

ChemScan® mini oP

ORTHO PHOSPHORUS



Mini Size
Mini Price
Mini Maintenance
Maxi Value!

The new single parameter in-line analyzer family from ASA Analytics utilizes years of ChemScan® experience and proven technology to provide reliable and accurate analysis of water and waste water. This device has been designed from the ground up to reduce maintenance requirements, includes large ID sample tubing to minimize plugging and only needs quarterly reagent change out.

FEATURES

Automatic Analysis Utilizing ChemScan's Proven VMO Method

Low Maintenance

Automatic Zeroing and Cleaning

Proven Sample Handling with Large I.D. Flow Paths

Simple Field Adjustable Calibration

Sample Blank to Eliminate Background Interference

APPLICATIONS

Potable Water

Waste Water Effluent

CAPABILITIES

Automatic Analysis

Continuous Output

Multiple Data Communication Interface Options

BENEFITS

High Reliability

Low Capital Cost

Low Operating Cost

EPA Recognized Analysis Method

SPECIFICATIONS

Range (as PO ₄ - P):	0.03 - 3.0 ppm (Std), 0.1 - 6.0 ppm
Accuracy:	2% of value or 2x detection limit (whichever greater)
Cycle Time:	5 minutes to 9999 minutes (field programmable)
Environment:	5 - 50 degrees C
Power:	100 - 240 VAC, 50 W
Enclosure:	NEMA 4x
Safety Approval:	CSA-US
Sample:	0.5 - 1 Liter/analysis, pressure 5 ft to 10 psi
Maintenance:	Reagent replacement every 3 months, pump kit yearly
Relay Contacts:	1 SPDT Concentration, 1 SPDT Programmable
Serial Interface:	Serial, RS-232, RTU
Analog Output:	Isolated 4-20 mA



asa 
ANALYTICS

"Monitoring a World of Water"

Royce Water Technologies Pty Ltd



Rod: 0428 571 234 Qld, NT, Nth NSW & NZ
Tim: 0408 079 073 NSW & ACT
Arthur: 0439 337 247 Vic & Tas
Glenn: 0420 978 243 SA & WA
Web Site: www.roycewater.com.au
Email: contact@roycewater.com.au