

# Mini Mono & FreeAm

## Monochloramine analyser

The single parameter in-line analyser family from ChemScan® utilises years of experience and proven technology to provide reliable and accurate analysis of water and waste water.

This device has been designed from the ground up to reduce maintenance requirements, includes large ID sample tubing to minimise plugging and only needs quarterly reagent refills.

#### **Features**

- Automatic Analysis Utilising Proven Method
- Low Maintenance
- Proven Sample Handling with Large I.D. Flow Paths
- Simple Field Adjustable Calibration
- Sample Blank to Eliminate Backgound Interference
- Automatic Cleaning

#### **Benefits**

- High Reliability
- Low Capital Cost
- High Accuracy
- Low Operating Cost

#### **Capabilities**

- Automatic Analysis
- Continuous Output
- Multiple Data Communication Interface Options

#### **Applications**

- Potable Water
- Wastewater Effluent



### **Technical Specifications**

Range	0.02 - 10.0 mg/L (ppm)
Accuracy	5% of value or 2x detection limit (whichever is greater)
Cycle Time	5 minutes to 9999 minutes (field programmable)
Environment	5 - 50 degrees C (method dependent)
Power	100 - 240 VAC, 50 W
Enclosure	NEMA 4x
Safety Approval	CSA-US
Sample Requirements	0.5 - 1 Liter/analysis, pressure 2 to 10 psi, <150 mg/L TSS, <60 NTU
Maintenance	Reagent replacement every 3 months, pump kit yearly
Relay Contacts	1 SPDT Concentration, 1 SPDT Programmable
Serial Interface	RS-232 Maintenance Port
Analog Output	Isolated 4-20 mA